

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

1. (original) A machine implemented method for producing virtual camera motion, comprising the steps of:

receiving a set of two or more images of a scene;

identifying foreground for at least a subset of said images of said scene; and

creating a video of said scene conveying an illusion of a camera moving around said scene, said step of creating a video is based on said set of two or more images and said step of identifying foreground.

2. (currently amended) A machine implemented method for producing virtual camera motion according to claim 1, comprising:

receiving a set of two or more images of a scene;

identifying foreground for at least a subset of said images of said scene; and

creating a video of said scene conveying an illusion of a camera moving around said scene, said step of creating a video is based on said set of two or more images and said step of identifying foreground, wherein said step of identifying foreground comprises the steps of,

subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera,

subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera, and

creating a union of said first difference and said second difference, said union identifies said foreground.

3. (original) A method according to claim 2, wherein said step of identifying further

comprises the steps of:

- creating clusters of on pixels in said first difference;
- creating clusters of off pixels in said first difference;
- removing small clusters of on pixels in said first difference;
- filling in small clusters of off pixels in said first difference;
- creating clusters of on pixels in said second difference;
- creating clusters of off pixels in said second difference;
- removing small clusters of on pixels in said second difference; and
- filling in small clusters of off pixels in said second difference.

4. (original) A method according to claim 3, wherein said step of identifying further comprises the steps of:

- filtering said first difference;
- filtering said second difference; and
- filtering said union.

5. (original) A method according to claim 3, wherein said step of identifying further comprises the steps of:

- creating clusters of on pixels in said union;
- creating clusters of off pixels in said union;
- removing small clusters of on pixels in said union; and
- filling in small clusters of off pixels in said union.

6. (currently amended) A machine implemented method for producing virtual camera motion according to claim 1, comprising:

- receiving a set of two or more images of a scene;
- identifying foreground for at least a subset of said images of said scene; and
- creating a video of said scene conveying an illusion of a camera moving around said scene, said step of creating a video is based on said set of two or more images and said step of

identifying foreground, wherein<sub>1</sub>[[;]]

said step of receiving includes receiving a first video image, a second video image and a third video image<sub>1</sub>[[;]]

said first video image views a foreground object at a first angle<sub>1</sub>[[;]]

said second video image views said foreground object at a second angle<sub>1</sub>[[;]]

said third video image views said foreground object at a third angle<sub>1</sub>[[;]]

said step of creating a video includes creating a first set of one or more new video images and a second set of one or more video images<sub>1</sub>[[;]]

said first set of one or more video images appear to view said foreground object at angles between said first angle and said second angle<sub>1</sub>[[;]]

said second set of one or more video images appear to view said foreground object at angles between said second angle and said third angle<sub>1</sub>[[;]] and

said video includes said first set of one or more video images and said second set of one or more video images.

7. (original) A method according to claim 6, wherein:

said video further includes at least a portion of said first video image prior to said first set of one or more video images, at least a portion of said second video image prior to said second set of one or more video images and at least a portion of said third video image subsequent to said second set of one or more video images.

8. (original) A method according to claim 6, wherein said step of creating a video includes the step of:

creating one or more blurred backgrounds based on said step of identifying foreground, said first set of one or more video images and second set of one or more video images include said blurred backgrounds.

9. (original) A method according to claim 6, wherein said step of creating a video includes the step of:

creating one or more solid backgrounds based on said step of identifying foreground, said first set of one or more video images and second set of one or more video images include said solid backgrounds.

10. (original) A method according to claim 6, wherein said step of creating a first set of one or more video images comprises the steps of:

blending said first video image with said second image using different blending factors to create different backgrounds for said first set of one or more video images; and

blurring said backgrounds of said first set one or more video images using different blurring factors for at least a subset of said one or more video images.

11. (original) A method according to claim 10, wherein said step of identifying foreground comprises the steps of:

subtracting a fourth video image from said first video image to create a first difference, said fourth video image and said second video image are from a first camera;

subtracting a fifth video image from said second video image to create a second difference, said fifth image is from said first camera; and

creating a union of said first difference and said second difference, said union identifies said foreground.

12. (original) A method according to claim 6, wherein creating a first set of one or more video images comprises the steps of:

finding edges in said first video image;

finding edges in said second video image;

finding edges in said third video image;

creating matches of at least portions of edges in said first video image, said second video image and said third video image;

creating chains of said matches;

discarding bad chains; and

creating morphs of at least a portion of said first video image and said second video image based on said chains.

13. (original) A method according to claim 6, wherein creating a first set of one or more video images comprises the steps of:

identifying edges in said first video image and said second video image;  
interpolating positions for said edges in said first set of one or more video images; and  
blending regions of said first video image between said edges with regions of said second video image between said edges according to different blending factors for each of said first set of one or more new video images, said blending factors correlate to said interpolated positions.

14. (original) A method according to claim 1, wherein:  
said scene appears frozen in time in said illusion of said camera moving around said scene.

15. (original) A method according to claim 1, wherein said step of creating a video comprises the steps of:

warping a first image from a first camera to a second image from a second camera;  
warping a third image from a third camera to said second image from said second camera;  
removing foregrounds from said first image, said second image and said third image;  
filling in background for said removed foreground in said first image, said second image and said third image;  
creating new images by blending backgrounds of said first image with said second image and said second image with said third image;  
blurring said new images;  
morphing said removed foregrounds;  
adding said morphed foregrounds to said new images; and  
unwarping said new images.

16. (original) A method according to claim 1, wherein said step of creating includes the steps of:

creating one or more video images having blurred backgrounds based on said step of identifying foreground; and

assembling said created one or more video images into said video.

17. (original) A method according to claim 1, wherein said step of creating includes the steps of:

creating one or more video images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more video images;

blurring said backgrounds of said one or more video images using different blurring factors for at least a subset of said one or more video images; and

assembling said created one or more video images into said video.

18. (original) A method according to claim 1, wherein said step of creating includes the steps of:

creating one or more video images having solid backgrounds based on said step of identifying foreground, said video includes said video images having solid backgrounds; and assembling said created one or more video images into said video.

19. (original) A method according to claim 1, wherein said step of creating comprises the steps of:

finding edges in a first video image from a first camera;

finding edges in a second video image from a second camera;

finding edges in a third video image from a third camera;

creating matches of at least portions edges in said first video image, said second video image and said third video image;

creating chains of said matches;  
discarding bad chains;  
creating morphs of at least a portion of said first video image and said second video image based on said chains;  
creating a new set of video images, adding said morphs to said new set of video images;  
and  
assembling said new set of images into said video.

20. (original) A machine implemented method for producing virtual camera motion, comprising the steps of:

receiving two or more images of a scene which view a foreground object from a first set of different angles;

identifying foreground for said two or more images of said scene; and

creating one or more new images of said scene based on said two or more images and step of identifying, said new images appear to view said foreground object from new angles different than said first set of different angles.

21. (original) A method according to claim 20, wherein said step of identifying foreground comprises the steps of:

subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera;

subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera; and

creating a union of said first difference and said second difference, said union identifies said foreground.

22. (original) A method according to claim 20, further comprising the step of:

assembling said new images of said scene into a movie that conveys the illusion of a camera moving around said scene as said scene appears frozen in time.

23. (original) A method according to claim 20, wherein:  
said one or more video images are created with blurred backgrounds based on said step of identifying foreground.

24. (original) A method according to claim 20, wherein said step of creating one or more new images comprises the steps of:

creating said one or more new images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more new images;

blurring said backgrounds of said one or more new images using different blurring factors for at least a subset of said one or more new images; and

assembling said created one or more video images into a video.

25. (original) A method according to claim 20, wherein said step of creating one or more new images comprises the steps of:

creating said one or more new images having solid backgrounds based on said step of identifying foreground; and

assembling said created one or more video images into said video.

26. (original) A method according to claim 20, wherein said step of creating one or more new images comprises the steps of:

finding edges in a first video image from a first camera, said two or more images of a scene include said first video image;

finding edges in a second video image from a second camera, said two or more images of a scene include said second video image;

finding edges in a third video image from a third camera, said two or more images of a scene include said third video image;

creating matches of at least portions edges in said first video image, said second video



image and said third video image;  
creating chains of said matches;  
discarding bad chains;  
creating morphs of at least a portion of said first video image and said second video image based on said chains;  
creating a new set of video images, adding said morphs to said new set of video images;  
and  
assembling said new set of images into a video.

27. (original) A machine implemented method for identifying foreground, comprising the steps of:

receiving a first image from a first camera;  
receiving a second image from said first camera;  
receiving a third image from said first camera;  
subtracting said second image from said first image to create a first difference  
subtracting said third image from said first image to create a second difference; and  
creating a union of said first difference and said second difference, said union identifies said foreground.

28. (original) A method according to claim 27, further comprising the steps of:

creating clusters of on pixels in said first difference;  
creating clusters of off pixels in said first difference;  
removing small clusters of on pixels in said first difference;  
filling in small clusters of off pixels in said first difference;  
creating clusters of on pixels in said second difference;  
creating clusters of off pixels in said second difference;  
removing small clusters of on pixels in said second difference; and  
filling in small clusters of off pixels in said second difference.

29. (original) A method according to claim 28, further comprising the steps of:  
filtering said first difference;  
filtering said second difference; and  
filtering said union.

30. (original) A method according to claim 28, further comprising the steps of:  
creating clusters of on pixels in said union;  
creating clusters of off pixels in said union;  
removing small clusters of on pixels in said union; and  
filling in small clusters of off pixels in said union.

31. (original) One or more processor readable storage devices having processor readable code embodied on said processor readable storage devices, said processor readable code for programming one or more processors to perform a method comprising the steps of:  
receiving a set of two or more images of a scene;  
identifying foreground for at least a subset of said images of said scene; and  
creating a video of said scene conveying an illusion of a camera moving around said scene, said step of creating a video is based on said set of two or more images and said step of identifying foreground.

32. (original) One or more processor readable storage devices according to claim 31, wherein said step of identifying foreground comprises the steps of:  
subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera;  
subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera; and  
creating a union of said first difference and said second difference, said union identifies said foreground.

33. (original) One or more processor readable storage devices according to claim 31, wherein said step of creating includes the steps of:

creating one or more video images having blurred backgrounds based on said step of identifying foreground; and

assembling said created one or more video images into said video.

34. (original) One or more processor readable storage devices according to claim 31, wherein said step of creating includes the steps of:

creating one or more video images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more video images;

blurring said backgrounds of said one or more video images using different blurring factors for at least a subset of said one or more video images; and

assembling said created one or more video images into said video.

35. (original) One or more processor readable storage devices according to claim 31, wherein said step of creating comprises the steps of:

finding edges in a first video image from a first camera;

finding edges in a second video image from a second camera;

finding edges in a third video image from a third camera;

creating matches of at least portions edges in said first video image, said second video image and said third video image;

creating chains of said matches;

discarding bad chains;

creating morphs of at least a portion of said first video image and said second video image based on said chains;

creating a new set of video images, adding said morphs to said new set of video images; and

assembling said new set of images into said video.

36. (original) One or more processor readable storage devices according to claim 31, wherein said step of creating a video comprises the steps of:

- warping a first image from a first camera to a second image from a second camera;
- warping a third image from a third camera to said second image from said second camera;
- removing foregrounds from said first image, said second image and said third image;
- filling in background for said removed foreground in said first image, said second image and said third image;
- creating new images by blending backgrounds of said first image with said second image and said second image with said third image;
- blurring said new images;
- morphing said removed foregrounds;
- adding said morphed foregrounds to said new images; and
- unwarping said new images.

37. (original) An apparatus, comprising:

- a communication interface;
- one or more storage devices; and
- one or more processors in communication with said one or more storage devices and said communication interface, said one or more processors programmed to perform a method comprising the steps of:

- receiving a set of two or more images of a scene,
- identifying foreground for at least a subset of said images of said scene, and
- creating a video of said scene conveying an illusion of a camera moving around said scene frozen in time, said step of creating a video is based on said set of two or more images and said step of identifying foreground.

38. (original) An apparatus according to claim 37, wherein said step of identifying

foreground comprises the steps of:

subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera;

subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera; and

creating a union of said first difference and said second difference, said union identifies said foreground.

39. (original) An apparatus according to claim 37, wherein said step of creating includes the steps of:

creating one or more video images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more video images;

blurring said backgrounds of said one or more video images using different blurring factors for at least a subset of said one or more video images; and

assembling said created one or more video images into said video.

40. (original) An apparatus according to claim 39, further comprising:

three cameras;

camera control electronics connected to said camera;

synchronization electronics in communication with said camera control electronics; and

one or more time code inserters in communication with said camera control electronics and said processor, said cameras capture said two or more images of said scene, said time code inserters insert time codes into said two or more images of said scene including said first image and said second image, said step of creating one or more video images by blending uses said time codes in said first image and said second image.

41. (currently amended) ~~One or more processor readable storage devices~~ An apparatus according to claim 37, wherein said step of creating includes the steps of:

creating one or more video images having blurred backgrounds based on said step of identifying foreground; and

assembling said created one or more video images into said video.

42. (original) One or more processor readable storage devices having processor readable code embodied on said processor readable storage devices, said processor readable code for programming one or more processors to perform a method comprising the steps of:

receiving two or more images of a scene which view a foreground object from a first set of different angles;

identifying foreground for said two or more images of said scene; and

creating one or more new images of said scene based on said two or more images and step of identifying, said new images appear to view said foreground object from new angles different than said first set of different angles.

43. (original) One or more processor readable storage devices according to claim 42, wherein said step of identifying foreground comprises the steps of:

subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera;

subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera; and

creating a union of said first difference and said second difference, said union identifies said foreground.

44. (original) One or more processor readable storage devices according to claim 42, wherein said method further comprises the step of:

assembling said new images of said scene into a movie that conveys the illusion of a camera moving around said scene as said scene appears frozen in time.

45. (original) One or more processor readable storage devices according to claim 42,

wherein said step of creating one or more new images comprises the steps of:

creating said one or more new images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more new images;

blurring said backgrounds of said one or more new images using different blurring factors for at least a subset of said one or more new images; and

assembling said created one or more video images into a video.

46. (original) One or more processor readable storage devices according to claim 42, wherein said step of creating one or more new images comprises the steps of:

finding edges in a first video image from a first camera, said two or more images of a scene include said first video image;

finding edges in a second video image from a second camera, said two or more images of a scene include said second video image;

finding edges in a third video image from a third camera, said two or more images of a scene include said third video image;

creating matches of at least portions edges in said first video image, said second video image and said third video image;

creating chains of said matches;

discarding bad chains;

creating morphs of at least a portion of said first video image and said second video image based on said chains;

creating a new set of video images, adding said morphs to said new set of video images; and

assembling said new set of images into a video.

47. (original) An apparatus, comprising:

a communication interface;

one or more storage devices; and

one or more processors in communication with said one or more storage devices and said communication interface, said one or more processors programmed to perform a method comprising the steps of:

- receiving two or more images of a scene which view a foreground object from a first set of different angles,
- identifying foreground for said two or more images of said scene, and
- creating one or more new images of said scene based on said two or more images and step of identifying, said new images appear to view said foreground object from new angles different than said first set of different angles.

48. (original) An apparatus according to claim 47, wherein said step of identifying foreground comprises the steps of:

- subtracting a first image of said scene from a second image of said scene to create a first difference, said first image and said second image are from a first camera;
- subtracting a third image of said scene from said second image to create a second difference, said third image is from said first camera; and
- creating a union of said first difference and said second difference, said union identifies said foreground.

49. (original) An apparatus according to claim 47, wherein said step of creating one or more new images comprises the steps of:

- creating said one or more new images by blending a first image from a first camera with a second image from a second camera using different blending factors to create different backgrounds for said one or more new images;
- blurring said backgrounds of said one or more new images using different blurring factors for at least a subset of said one or more new images; and
- assembling said created one or more video images into a video.

50. (original) An apparatus according to claim 49, further comprising:



three cameras;  
camera control electronics connected to said camera;  
synchronization electronics in communication with said camera control electronics; and  
one or more time code inserters in communication with said camera control electronics  
and said processor, said cameras capture said two or more images of said scene, said time code  
inserters insert time codes into said two or more images of said scene including said first image  
and said second image, said step of creating one or more video images by blending uses said  
time codes in said first image and said second image.

51. (original) An apparatus according to claim 47, wherein said method further  
comprises the step of:

assembling said new images of said scene into a movie that conveys the illusion of a  
camera moving around said scene as said scene appears frozen in time.

52. (original) An apparatus according to claim 51, wherein said step of creating one  
or more new images comprises the steps of:

finding edges in a first video image from a first camera, said two or more images of a  
scene include said first video image;

finding edges in a second video image from a second camera, said two or more images  
of a scene include said second video image;

finding edges in a third video image from a third camera, said two or more images of a  
scene include said third video image;

creating matches of at least portions edges in said first video image, said second video  
image and said third video image;

creating chains of said matches;

discarding bad chains;

creating morphs of at least a portion of said first video image and said second video  
image based on said chains;

creating a new set of video images, adding said morphs to said new set of video images;

and

assembling said new set of images into a video.

53. (original) One or more processor readable storage devices having processor readable code embodied on said processor readable storage devices, said processor readable code for programming one or more processors to perform a method comprising the steps of:

- receiving a first image from a first camera;
- receiving a second image from said first camera;
- receiving a third image from said first camera;
- subtracting said second image from said first image to create a first difference
- subtracting said third image from said first image to create a second difference; and
- creating a union of said first difference and said second difference, said union identifies said foreground.

54. (original) One or more processor readable storage devices according to claim 53, wherein said method further comprises the steps of:

- creating clusters of on pixels in said first difference;
- creating clusters of off pixels in said first difference;
- removing small clusters of on pixels in said first difference;
- filling in small clusters of off pixels in said first difference;
- creating clusters of on pixels in said second difference;
- creating clusters of off pixels in said second difference;
- removing small clusters of on pixels in said second difference; and
- filling in small clusters of off pixels in said second difference.

55. (original) One or more processor readable storage devices according to claim 54, wherein said method further comprises the steps of:

- filtering said first difference;
- filtering said second difference; and

filtering said union.

56. (original) One or more processor readable storage devices according to claim 53, wherein said method further comprises the steps of:

- creating clusters of on pixels in said union;
- creating clusters of off pixels in said union;
- removing small clusters of on pixels in said union; and
- filling in small clusters of off pixels in said union.

57. (original) An apparatus, comprising:

- a communication interface;
- one or more storage devices; and

one or more processors in communication with said one or more storage devices and said communication interface, said one or more processors programmed to perform a method comprising the steps of:

- receiving a first image from a first camera,
- receiving a second image from said first camera,
- receiving a third image from said first camera,
- subtracting said second image from said first image to create a first difference,
- subtracting said third image from said first image to create a second difference,
- and
- creating a union of said first difference and said second difference, said union identifies said foreground.

58. (original) An apparatus according to claim 57, wherein said method further comprises the steps of:

- creating clusters of on pixels in said first difference;
- creating clusters of off pixels in said first difference;
- removing small clusters of on pixels in said first difference;

filling in small clusters of off pixels in said first difference;  
creating clusters of on pixels in said second difference;  
creating clusters of off pixels in said second difference;  
removing small clusters of on pixels in said second difference; and  
filling in small clusters of off pixels in said second difference.

59. (original) An apparatus according to claim 58, wherein said method further comprises the steps of:

filtering said first difference;  
filtering said second difference; and  
filtering said union.

60. (original) An apparatus according to claim 57, wherein said method further comprises the steps of:

creating clusters of on pixels in said union;  
creating clusters of off pixels in said union;  
removing small clusters of on pixels in said union; and  
filling in small clusters of off pixels in said union.